

WINDOW TECHNOLOGY DOOR TECHNOLOGY AUTOMATIC ENTRANCE SYSTEMS **BUILDING MANAGEMENT SYSTEMS** 



HS SilentClose soft-close damper for Lift&Slide elements





5

# **Comfort and security combined**

Added value for the end customer



# GU

## HS SilentClose soft-close damper for Lift&Slide elements

The HS SilentClose soft-close damper gently brakes the Lift&Slide sash as it opens or closes and moves it to the respective end position. It can be installed fully concealed and is available in two sizes, for sash weights up to 200 kg and 400 kg respectively. The combination with HS StopUnit on the same sash is possible (for open and closed position). Opening and closing can be controlled separately via both products.

### **Fabricator benefits:**

- Fast and straightforward installation
- Pre-mounted components
- Suitable for all customary sash arrangement patterns
- For sash weights up to 200 kg and 400 kg
- The damping unit can be easily replaced simply by loosening a screw and without having to take off the Lift&Slide sash
- Universally usable damping unit for all profile materials

### Benefits for end customer:

- Sophisticated design and aesthetics: all elements are concealed
- Outstanding operating convenience when opening and closing: the Lift&Slide sash is braked automatically and guided to the end position
- Nothing needs to be repositioned or modified when operating the Lift&Slide door
- Danger of entrapment is significantly reduced as the sash closes slowly
- The soft-close damper reliably prevents the sash from striking against the frame and damaging it



Gretsch-Unitas GmbH Baubeschläge | Johann-Maus-Str. 3 | 71254 Ditzingen, Germany | Tel. + 49 7156 301-0 | www.g-u.com