

Materialprüfungsamt Nordrhein-Westfalen

Prüfen • Überwachen • Zertifizieren

Certificate of constancy of performance

0432-CPR-00029-02

Version 12

In compliance with Regulation (EU) No 305/2011 of the European Parliament and of the Council of 9 March 2011 (the Construction products Regulation or CPR), this certificate applies to the construction product

Panic exit devices GU BKS for wide stile doors

Panic exit devices operated by a horizontal bar for single or double leaf doors for use on escape routes with the intended use according to annex 1 and as detailed and classified in annex 2,

placed on the market under the name or trade mark of

BKS GmbH

Heidestrasse 71
42549 Velbert
Germany

and produced in the manufacturing plant(s)

according to the assignment of devices in annex 2

This certificate attests that all provisions concerning the assessment and verification of constancy of performance described in annex ZA of the standard(s)

EN 1125:2008

under **system 1** for the performance set out in this certificate are applied and that the factory production control conducted by the manufacturer is assessed to ensure the

constancy of performance of the construction product.

This certificate was first issued on 01.04.2015 and will remain valid until 30.03.2025 as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, unless suspended or withdrawn by the notified product certification body.

Dortmund, 21.06.2023



By order

RBA T. Meinks

Deputy Head of Certification Body Department
22.30.2

This Certificate consists of 1 page and 4 annexes.

This Certificate replaces the Certificate no. 0432-CPR-00029-02 dated
05.12.2022, Version 11.



The original of this document was issued in German language.

In case of doubt only the German version is valid.

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Intended use:

For use on single and double leaf door in escape routes

Essential characteristic	Requirement clauses EN 1125: 2008	Performance
Ability to release (for locked doors in escape routes)	4.2.1 Threshold according to table 1 Release function Design bar Bar projection Intended use for the door Door free movement Door mass and dimensions Access from outside Release forces Security requirement	≤ 1S: passed Type A (touch bar): passed Type B (push bar): passed w ≤ 100 mm or 150 mm depending on model Grade A, B or C: passed passed Class 7:(door mass 300 kg): passed (dimensions 1500 mm width, 4500mm height):passed Passed (≤ 80 N, ≤ 220 N under pressure): passed (Class 1, 1000 N) passed
Durability of ability to release against aging and degradation (for locked doors on escape routes)	4.2.1 Threshold according to table 1 Corrosion resistancet Temperature range Re-engagement force Durability Abuse resistance –Horizontal bar Final examination	passed Class 3 (96 h, ≤ 120 N) passed (-10°C up to +60°C, ≤ +50 %) passed (≤ 50 N) passed (intended use for the door Class A, B: 200,000 cycles): Grade 7: passed (intended use for the door Grade C: 20,000 cycles, Class 7) passed (500 N, 1000 N): passed (Release force (≤ 80 N, ≤ 220 N under pressure): passed (Door face gap R ≥25 mm): passed Door free movement) passed
Self-closing ability C (for fire/smoke doors on escape routes)	4.2.1 Threshold according to table 1 Re-engagement force	(≤ 50 N) passed
Durability of Self closing ability C against aging and degradation (for fire/smoke doors on escape routes)	4.2.1 Threshold according to table 1 Durability Re-engagement force	(Application range of the door Class A, B: 200,000 cycles, Class 7): passed (Application range of the door Class C: 20,000 cycles, Class 7) passed (≤ 50 N) passed
Resistance to fire E (integrity) and I(insulation) (for use on fire doors on escape routes)	4.2.1 Threshold according to table 1, annex B	Class 0: NPD Class B: passed
Control of dangerous substances	4.1.29 Note 2 in ZA.1	According to the manufacturer the materials in the door closer do not contain or release any dangerous substances in excess of maximum levels specified in existing European material standards or any national regulations

Panic exit devices series 21xx

Devices

Manufacturing plant DO 5.0

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification	C M B																				
	B-2100x ^{b)}	B	IV	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2100x ^{b)}	B	IV	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2101x ^{b)}	A	IV	55 – 100 mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2101x ^{b)}	A	IV	55 – 100 mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2102x ^{b)}	B	V	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2102x ^{b)}	B	V	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2103x ^{b)}	A	V	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2103x ^{b)}	A	V	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2106x ^{b)}	B	I	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2106x ^{b)}	B	I	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2107x ^{b)}	A	I	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2107x ^{b)}	A	I	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2110x ^{b)}	B	IV	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2110x ^{b)}	B	IV	55 – 100mm	78mm RZ/PZ	≥ 18 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2111x ^{b)}	A	IV	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2111x ^{b)}	A	IV	55 – 100mm	78mm RZ/PZ	≥ 18 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2112x ^{b)}	B	V	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2112x ^{b)}	B	V	55 – 100mm	78mm RZ/PZ	≥ 18 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2113x ^{b)}	A	V	55 – 100 mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2113x ^{b)}	A	V	55 – 100 mm	78mm RZ/PZ	≥ 18 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2116x ^{b)}	B	I	55 – 100 mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2116x ^{b)}	B	I	55 – 100 mm	78mm RZ/PZ	≥ 18 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2117x ^{b)}	A	I	55 – 100 mm	72 mm PZ, 74 mm RZ,	≥ 20 mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification	CMB																				
	S-2117x ^{b)}	A	I	55 – 100 mm	78mm RZ/PZ	≥ 18 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2156x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2157x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2160x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2161x ^{b)}	A	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2162x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2163x ^{b)}	A	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2166x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2170x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2171x ^{b)}	A	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B2172 ^{b)}	B	V	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2180x ^{b)}	B	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2181x ^{b)}	A	S	55 – 100mm	72 mm PZ, 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	5320 ^{b)} SE - lock	A	V	55 – 100 mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	5321 ^{b)} SE - lock	A	V	55 – 100 mm	72 mm PZ, 74 mm RZ	≥ 20 mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification	CMB																				
1	B2189	C	-	55 – 100 mm	-	≥ 20 mm	Switching lock B1895, top shoot bolt B9036, bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B9028/B-0028x	<table border="1"> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td> </tr> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td> </tr> </table> <p>Advice on accessories: see list 0-47351-L0-0</p>	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				
2	B2190	C	-	55 – 100 mm	-	≥ 20 mm	Switching lock B1895, top shoot bolt B9036, bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B9028/B-0028x	<table border="1"> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td> </tr> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td> </tr> </table> <p>Advice on accessories: see list 0-47351-L0-0</p>	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				
3	B-2193	C	-	65 – 100 mm	-	≥ 20 mm	Switching lock B1895, top shoot bolt B9036, bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B9028/B-0028x	<table border="1"> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td> </tr> <tr> <td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td> </tr> </table> <p>Advice on accessories: see list 0-47351-L0-0</p>	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				

Panic exit devices series 23xx

Devices

Manufacturing plant DO 5.0

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification										C M B
								3	7	7	B	1	3	2	1	A	B	
	1201 ^{a)}	B	I, III, IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	1	A	B	
	B-1201 ^{a)}	B	I, III, IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	2	B	B	
	B-2320x ^{b)}	B	IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	1	A	B	
	S-2320x ^{b)}	B	IV	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	B	
	B-2321x ^{b)}	A	IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	2	B	A	4-6
	S-2321x ^{b)}	A	IV	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	A	4-6
	B-2322x ^{b)}	B	V	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	2	B	B	
	S-2322x ^{b)}	B	V	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	B	
	B-2323x ^{b)}	A	V	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	2	B	A	4-6
	S-2323x ^{b)}	A	V	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	A	4-6
	B-2324x ^{b)}	B	III	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	2	B	B	
	S-2324x ^{b)}	B	III	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	B	
	B-2325x ^{b)}	A	III	55 –100mm	72 mm PZ 74 mm R	≥ 20 mm		3	7	7	B	1	3	2	2	B	A	4-6
	S-2325x ^{b)}	A	III	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	1	A	A	4-6
	B-2326x ^{b)}	B	I	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	1	A	B	
	S-2326x ^{b)}	B	I	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	2	B	B	
	B-2327x ^{b)}	A	I	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm		3	7	7	B	1	3	2	1	A	A	4-6
	S-2327x ^{b)}	A	I	55 –100mm	78mm RZ/PZ	≥ 18 mm		3	7	7	B	1	3	2	2	B	A	4-6
	B-2330x ^{b)}	B	IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	3	7	7	B	1	3	2	1	A	B	
	S-2330x ^{b)}	B	IV	55 –100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	3	7	7	B	1	3	2	2	B	B	
	B-2331x ^{b)}	A	IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	3	7	7	B	1	3	2	1	A	A	4-6
	S-2331x ^{b)}	A	IV	55 –100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	3	7	7	B	1	3	2	2	B	A	4-6

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification	C M B																				
	B-2332x ^{b)}	B	V	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2332x ^{b)}	B	V	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2333x ^{b)}	A	V	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2333x ^{b)}	A	V	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2334x ^{b)}	B	III	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2334x ^{b)}	B	III	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2335x ^{b)}	A	III	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2335x ^{b)}	A	III	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2336x ^{b)}	B	I	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	S-2336x ^{b)}	B	I	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																				
3	7	7	B	1	3	2	2	B	B																				
	B-2337x ^{b)}	A	I	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	S-2337x ^{b)}	A	I	55 – 100mm	78mm RZ/PZ	≥ 18 mm	Snap lock B1795/B1796, Shoot bolt B9006	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	4-6
3	7	7	B	1	3	2	1	A	A																				
3	7	7	B	1	3	2	2	B	A																				
	B-2340x version 2P ^{b)}	B	IV	55 – 100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table>	3	7	7	0	1	3	2	1	A	B	3	7	7	0	1	3	2	2	B	B	
3	7	7	0	1	3	2	1	A	B																				
3	7	7	0	1	3	2	2	B	B																				

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

No	Item no.	VS-type	Function	Backset	Distance	Forend width	Accessories	Classification	CMB																				
	B-2341x version 2P ^{b)}	A	IV	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	0	1	3	2	1	A	A	3	7	7	0	1	3	2	2	B	A	4-6
3	7	7	0	1	3	2	1	A	A																				
3	7	7	0	1	3	2	2	B	A																				
	B-2342x version 2P ^{b)}	B	V	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	0	1	3	2	1	A	B	3	7	7	0	1	3	2	2	B	B	
3	7	7	0	1	3	2	1	A	B																				
3	7	7	0	1	3	2	2	B	B																				
	B-2343x version 2P ^{b)}	A	V	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	0	1	3	2	1	A	A	3	7	7	0	1	3	2	2	B	A	4-6
3	7	7	0	1	3	2	1	A	A																				
3	7	7	0	1	3	2	2	B	A																				
	B-2344x version 2P ^{b)}	B	III	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	0	1	3	2	1	A	B	3	7	7	0	1	3	2	2	B	B	
3	7	7	0	1	3	2	1	A	B																				
3	7	7	0	1	3	2	2	B	B																				
	B-2345x version 2P ^{b)}	A	III	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	0	1	3	2	1	A	A	3	7	7	0	1	3	2	2	B	A	4-6
3	7	7	0	1	3	2	1	A	A																				
3	7	7	0	1	3	2	2	B	A																				
	B-2346x version 2P ^{b)}	B	I	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr></table>	3	7	7	0	1	3	2	1	A	B	3	7	7	0	1	3	2	2	B	B	
3	7	7	0	1	3	2	1	A	B																				
3	7	7	0	1	3	2	2	B	B																				
	B-2347x version 2P ^{b)}	A	I	55 –100mm	72 mm PZ 74 mm RZ	≥ 20mm		<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr><tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr></table>	3	7	7	0	1	3	2	1	A	A	3	7	7	0	1	3	2	2	B	A	4-6
3	7	7	0	1	3	2	1	A	A																				
3	7	7	0	1	3	2	2	B	A																				
4	B2390	C	-	65 - 100 mm	-	≥ 20 mm	Switching lock B1895, top or top and bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B-0028/B-9003	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td></tr></table> Advice on accessories: see list 0-47351-L0-0	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				
5	B-2393	C	-	65 - 100 mm	-	≥ 20 mm	Switching lock B1895, top or top and bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B-0028/B-9003	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td></tr></table> Advice on accessories: see list 0-47351-L0-0	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				
6	B2392	C	-	65 - 100 mm	-	≥ 20 mm	Switching lock B1895, top or top and bottom shoot bolt B9006, shoot bolt guide B9019, floor keep B9009/B-9003, striking plate B9000, eccentric floor keep B-0028/B-9003 E-opener with Metö-function	<table border="1"><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>C</td></tr><tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>C</td></tr></table> Advice on accessories: see list 0-47351-L0-0	3	7	7	B	1	3	2	1	A	C	3	7	7	B	1	3	2	2	B	C	
3	7	7	B	1	3	2	1	A	C																				
3	7	7	B	1	3	2	2	B	C																				

Lock types B-2320x (S-2320x) to B-2337x (S-2337x) can be fitted with a secured latch locking clamp. The following then applies:

			0						
			0						

Striking plates B-9000, B-900xxxx

Lock types B-2320x (S-2320x) to B-2337x (S-2337x) can be fitted optionally with electric monitoring functions for the latch, follower, lock ward and bolt.

Lock types B-2320x (S-2320x) to B-2337x (S-2337x) can be fitted optionally, given suitable rebate space, with latch protrusion and bolt protrusion +1mm, +3mm or +5mm

Lock types B-232xx (S-232xx) can be converted to lock types B-233xx (S-233xx) and reverse.

Panic exit devices series Secury & Secury Automatic PA

Devices

Manufacturing plant DO 6.1

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	CMB																				
Secury 2110 B ^{b)}	B	IV	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Secury 2111 ^{b)}	A	IV	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																		
3	7	7	B	1	3	2	2	B	A																		
Secury 2112 C ^{b)}	B	V	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Secury 2113 ^{b)}	A	V	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																		
3	7	7	B	1	3	2	2	B	A																		
Secury 2116 E ^{b)}	B	I	55 – 100 mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Secury 2119 ^{b)}	A	I	55 – 100 mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																		
3	7	7	B	1	3	2	2	B	A																		
Secury 2170 C ^{b)}	B	V	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Secury 2171 ^{b)}	A	V	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																		
3	7	7	B	1	3	2	2	B	A																		
Secury 2166 ^{b)} with secured latch locking clamp	B	I	25 – 65mm	72mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	0	1	3	2	1	A	B	3	7	7	0	1	3	2	2	B	B	
3	7	7	0	1	3	2	1	A	B																		
3	7	7	0	1	3	2	2	B	B																		
Secury 2169 ^{b)} with secured latch locking clamp	A	I	25 – 65mm	72mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	0	1	3	2	1	A	A	3	7	7	0	1	3	2	2	B	A	
3	7	7	0	1	3	2	1	A	A																		
3	7	7	0	1	3	2	2	B	A																		

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	CMB																				
Secury 2116S ^{b)}	B	I	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	1-3
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Secury 2119S ^{b)}	B	I	55 – 100mm	72 mm PZ 74 mm RZ	≥16mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>A</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>A</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	A	3	7	7	B	1	3	2	2	B	A	1-3
3	7	7	B	1	3	2	1	A	A																		
3	7	7	B	1	3	2	2	B	A																		

The lock types shown above can be fitted optionally with electric monitoring functions for the latch, follower, lock ward and bolt.

The lock types shown above can be fitted optionally with latch protrusion +3mm or +5mm.

Lock types Secury 2170/71 are electrically couplable

The lock types Secury 2110 to 2119S can be fitted optionally with an electric drive (A opener).

The lock types shown above can be fitted optionally with an additional latchbolt.

Panic exit devices series SECURY ePOWER

Manufacturing plant DO 6.1

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	CMB																				
SECURY ePOWER PT1 B ^{b)}	B	VI	35 – 80mm	72mm PZ 74 mm RZ 92mm PZ 94 mm RZ	≥18mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>4</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>4</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	0	1	4	2	1	A	B	3	7	7	0	1	4	2	2	B	B	
3	7	7	0	1	4	2	1	A	B																		
3	7	7	0	1	4	2	2	B	B																		
SECURY ePOWER PE1 B ^{b)}	B	I	35 – 80mm	72mm PZ 74 mm RZ 92mm PZ 94 mm RZ	≥18mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>4</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>0</td><td>1</td><td>4</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	0	1	4	2	1	A	B	3	7	7	0	1	4	2	2	B	B	
3	7	7	0	1	4	2	1	A	B																		
3	7	7	0	1	4	2	2	B	B																		

Materialprüfungsamt Nordrhein-Westfalen

Prüfen · Überwachen · Zertifizieren

Item no.	VS-type	Function	Backset	Distance	Forend width	Classification	CMB																				
PA 400 ^{b)} PA 800 ^{b)} PA 1200 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
PAA 400 ^{b)} PAA 800 ^{b)} PAA 1200 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
PA 420 ^{b)} PA 820 ^{b)} PA 1220 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
PAA 420 ^{b)} PAA 820 ^{b)} PAA 1220 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Security Automatic 3 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
Security Automatic 6 ^{b)}	B	I	33-90mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		
GU-SECURY Automatic-DRP ^{b)}	B	I	33-80mm	72mm PZ 74mm RZ 78mm RZ 92mm PZ 94mm RZ	≥ 16 mm	<table border="1"> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>1</td><td>A</td><td>B</td></tr> <tr><td>3</td><td>7</td><td>7</td><td>B</td><td>1</td><td>3</td><td>2</td><td>2</td><td>B</td><td>B</td></tr> </table> <p>Advice on accessories: Take account of list 0-47351-L0-0-0</p>	3	7	7	B	1	3	2	1	A	B	3	7	7	B	1	3	2	2	B	B	
3	7	7	B	1	3	2	1	A	B																		
3	7	7	B	1	3	2	2	B	B																		

Designation in the certificate	Lock designation
PA 400 PA 800 PA 1200	Sec. A SF2 ...
PAA 400 PAA 800 PAA 1200	Sec. A SF2 ... A opener
PA 420 PA 820 PA 1200	Sec. A SFF2
PAA 420 PAA 820 PAA 1220	Sec. A SFF2 ... A opener

P: P = Panic function
A: A = Automatic
A: A = A opener
8: System: 4 = wood, 8 = aluminium, 12 = PVC
2: 0 = Latchbolt, 2 = double latchbolt
0: 0 = single leaf door

Lock types PA 400 – 1220, GU-SECURY Automatic-DRP and Security 1910 – 1919S can be operated with standalone additional latch at the lengthwise forend in combination with escape door opener EFF-EFF 332 as electrically locked panic lock (Security EVP). Panic function guaranteed only with unlocked (disconnected) door opener EFF-EFF 332. (Then only VS- type B).

Multipoint locking systems can be equipped optionally with automatic round bolts Ø11mm or flat latchbolts.

Touch bars / Push bars

All the locks shown in Annex 2 can be combined with the bars shown below.

Item no.	Type	Handle length	Handle tube	End caps	Manufacturer & manufacturing plant
B 71xx xxxx	A = Touch bar	1350 mm	Aluminium, stainless steel	Black plastic, aluminium, stainless steel	BKS GmbH DO 35.01
B-7400x	A = Touch bar	1350 mm	Aluminium, stainless steel	Aluminium, stainless steel	BKS GmbH DO 35.01
B-7401x	A = Touch bar	1350 mm	Aluminium, stainless steel	Aluminium, stainless steel	BKS GmbH DO 35.01
B-7402x	A = Touch bar	1350 mm	Stainless steel	Stainless steel	BKS GmbH DO 35.01
B-7403x	A = Touch bar	1350 mm	Aluminium, stainless steel	Aluminium, stainless steel	BKS GmbH DO 35.01
B-744xx	B = Push bar	1450 mm	Aluminium, stainless steel	Plastic, aluminium, stainless steel	BKS GmbH DO 35.01
B-744xx (EVT)	B = Push bar	1450 mm	Aluminium, stainless steel	Plastic, aluminium, stainless steel	BKS GmbH DO 35.01
PS 160 XA 30 PS 160 XA 40	A = Touch bar	1350 mm	Stainless steel	-	HEWI VE 30-26
PS 111 XA 30 PS 111 XA 40	A = Touch bar	1350 mm	Stainless steel	-	HEWI VE 30-26

Outside door handle

Manufacturer	Code
BKS	DO 20.10

Panic exit devices, general information

- a) In the case of cylinder locks (PZ, RZ) as standard or half cylinders, the escape door function of the lock is only guaranteed if the key is removed. Please note the permitted combinations of cylinder locks in combination with BKS panic locks. You can find an overview on our website www.g-u.com by going to Service / Downloads / Door technology.
- b) Cylinder locks of all types do not have any effect on the correct escape door function. Please note the permitted combinations of cylinder locks in combination with BKS panic locks. You can find an overview on our website www.g-u.com by going to Service / Downloads / Door technology.
- Max. door leaf weight: 300 kg
- Max. door leaf width: 1500mm
- Max. door leaf height: 4500mm
- Function I: One-piece lock follower, permanent escape door function.
Opening from the inside is always possible by means of the fitting. Opening is possible from the outside with key by means of the switch **Transformer change function E**.
- Function III: Divided lock follower, permanent escape door function from the inside.
Opening from the inside is always possible by means of the inside fitting. The outside fitting is permanently engaged or permanently disengaged by means of the key. The bolt is actuated from the outside only by the key. After actuation of the fitting from the inside, the door can be opened from the outside as well until manual relocking. **Gateway function D**.
- Function IV: Divided lock follower, permanent escape door function from the inside.
Opening from the inside is always possible by means of the inside fitting. The outside fitting is permanently engaged or permanently disengaged by means of the key. The bolt is actuated from the outside only by the key. After actuation of the fitting from the inside, the door cannot be opened by means of the fitting from the outside as well. **Changeover function B**.
- Function V: Divided lock follower, permanent escape door function from the inside.
Opening from the inside is always possible by means of the inside fitting. The outside fitting is disengaged as standard. The outside fitting can only be engaged by means of a specific key position. The outside fitting is disengaged again when the key is removed. **Forced lock function C**.
- Function VI: Divided lock follower, permanent escape door function from the inside.
Opening from the inside is always possible by means of the inside fitting. The outside fitting affects the main latch permanently. The bolt is actuated from the outside only by the key. Following activation of the daytime unlocking (no automatic motorised locking after the door is closed), the door is passable from the outside by actuating the fitting until the daytime unlocking is deactivated. **Door handle function T**.
- Function S: Special function as defined by the manufacturer. Permanent escape door function from the inside.



- VS type A: lock for a single or a double leaf door: active or inactive leaf.
- VS type B: Lock for single leaf doors
- VS type C: lock for a double leaf door: only inactive leaf
- Note 1: In conformity with the provisions of German building law, a lock of VS type B in accordance with EN 1125 (lock for single-leaf doors only) can also be used in the leaf of a double-leaf door if:
- a) the inactive leaf lock is secured against operating errors and
 - b) the passage width of the active leaf is sufficient as escape route width.
- Note 2: In the case of type C locks exclusively for the inactive leaf of double-leaf doors, in accordance with EN 1125 only 20,000 test cycles were carried out for verification of Class 7 durability (2nd digit).
- CMB: Indicates a combination of type A and type C lock for a double-leaf door that satisfies the requirements of EN 1125.
- Assembly specification 1: Before mechatronic door fittings are used it must be ensured that the fastening for the door fitting does not impact the lock system (lock case, locking bars, etc.). Likewise, the technical compatibility (e.g. rotation angle) between the lock and the door fitting must be checked.

Alternative and additional equipment

External access devices

Locking cylinders

Section 4.1.24 of EN 1125:2008 applies.

Outside door handle

Door handles according to DIN 18273 or special handle with an general building authority test certificate with a valid certificate of conformity can be used.

For devices type A or type B with function I, the following special handles may also be used as outside door handles:

- "Ixalo" system in accordance with general building authority approval no. Z-6.100-2593 from BKS GmbH, coded DO 5.0.
- Model series SALTO XS4 Original, series Ei4xx... and Ei6xx... in accordance with general building authority test certificate P-120003012, and model series SALTO XS4 One in accordance with general building authority test certificate P-120004926 from SALTO Systems S.L. coded DO 20.52
- Model series "CES OMEGA FLEX" in accordance with general building authority approval no. Z-6.100-2586 from C.Ed. Schulte GmbH, coded DO 20.38.
- Mechatronic fitting models Modelle SmartHandle AX, SmartHandle 3062, SmartHandle AX Advanced in accordance with general building authority approval no. Z-6.100-2594 from SimonsVoss Technologies GmbH, coded DO 20.57.
- Mechatronic fittings from the model series „DOM EniQ Guard“, „DOM ELS Guard“ and „DOM TapKey Guard“ in accordance with general building authority approval no. Z-6.100-2554 and models "DOM Guardian" in accordance with general building authority test certificate P-120003866.02 from DOM Sicherheitstechnik GmbH & Co. KG, coded DO 20.56.
- Mechatronic fittings from the model series "c-lever pro" and "c-lever compact" in accordance with general building authority approval no. Z-6.100-2516 from dormakaba Schweiz AG. Mechatronic fittings from the model series "c-lever pro" have to be coded with DO 6.21. Mechatronic fittings from the model series "c-lever compact" have to be coded with DO 20.61.
- Model series Dialock Türterminal DT 600 FH / DT 600c FH in accordance with general building authority approval no. Z-6.100-2577 from Häfele GmbH & Co KG, coded DO 20.36.

The classification shall be modified as appropriate in the absence of fire test evidence as follows:

			0					
--	--	--	---	--	--	--	--	--

In this case, the corresponding evidence must be requested separately from the handle manufacturers.

Specail versions

The locks for the inactive leaf of double leaf doors (VS-type C), drive bolt locks Art. No. B2189/B2190, B2390 and B2392 can also be used without bottom shoot bolt B9006.

Special locks

Locks B-1206x, B-2328x, B-2338x and B-2339x not shown above can be also used in the version as locks with latch only (without a deadbolt) for locks in accordance with EN 1125.

3	7	7	B	1	3	2	1	A	B
3	7	7	B	1	3	2	2	B	B

Special striking plates/electric strikes

Lock types B-2320x(S-2320x) to B-2337x(S-2337x) and B-1201 can be used with the following electric strikes for fire control doors without a change to the classification:

- EFF EFF:** 142, 143, 111, 331, 332, 118F
- GEZE/IST:** FT 200, FT 201, FT 500 – FT 503
- GU BKS:** B 9242 / 9243 Metö / No6 (FS) / B-9251 / B-9252 Metö (FS) / ET 8 (FS)

Electric strikes with daytime release function and / or stand-by current design are not permitted.

Lock types B-2320x(S-2320x) to B-2337x(S-2337x) and B-1201 can be used with the following electric strikes:

- EFF EFF:** 116, 118
- GEZE/IST:** IST 5000
- GU BKS:** No 5 / No 6 / B-9252 Metö / ET 8

The classification is then to be changed as follows:

			0						
--	--	--	---	--	--	--	--	--	--